




Features

- Low On resistance.
- 4.5V drive.
- RoHS compliant.



Package Dimensions

TO-252-5



N-Channel MOSFET

P-Channel MOSFET

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.06	4.83	0.160	0.190
B	0.76	1.02	0.030	0.040
C	0.36	0.64	0.014	0.025
C2	1.14	1.40	0.045	0.055
D	8.64	9.65	0.340	0.380
E	9.78	10.54	0.385	0.415
e	1.57	1.85	0.062	0.073
F	6.60	7.11	0.260	0.280
L	15.11	15.37	0.595	0.605
L2	-	1.40	-	0.055

Specifications

Absolute Maximum Ratings at $T_a=25^{\circ}\text{C}$

Parameter	Symbol	Conditions	N-Ch	P-Ch	Unit
Drain-to-Source Voltage	V_{DSS}		40	-40	V
Gate-to-Source Voltage	V_{GSS}		± 20	± 20	V
Drain Current (DC)	I_D		20	-15	A
Drain Current (Pulse)	I_{DP}	$PW \leq 10\mu\text{s}$, duty cycle $\leq 1\%$	35	-28	A
Allowable Power Dissipation	P_D	Mounted on a ceramic board (1000mm ² ×0.8mm) 1unit	30	30	W
Total Dissipation	P_T	Mounted on a ceramic board (1000mm ² ×0.8mm)	5	5	W
Avalanche Energy	E_{AS}	$T_J=25^{\circ}\text{C}$, $V_{DS}=20\text{V}$, $V_{GS}=10\text{V}$	60	60	mJ
Channel Temperature	T_{ch}		150	150	$^{\circ}\text{C}$

Si4044

Storage Temperature	T_{stg}		-55~+150	-55~+150	°C
---------------------	-----------	--	----------	----------	----

Electrical Characteristics (N-Channel) at $T_a=25^{\circ}\text{C}$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	40	-	-	V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=40\text{V}, V_{GS}=0\text{V}$	-	-	1	μA
Gate-to-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20\text{V}, V_{DS}=0\text{V}$	-	-	± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1	2	3	V
Static Drain-to-Source On-State Resistance	$R_{DS(ON)}$	$I_D=1\text{A}, V_{GS}=10\text{V}$	-	16	24	$\text{m}\Omega$
	$R_{DS(ON)}$	$I_D=1\text{A}, V_{GS}=4.5\text{V}$	-	25	35	$\text{m}\Omega$
Input Capacitance	C_{iss}	$V_{DS}=15\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$	-	980	-	pF
Output Capacitance	C_{oss}	$V_{DS}=15\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$	-	160	-	pF
Reverse Transfer Capacitance	C_{rss}	$V_{DS}=15\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$	-	110	-	pF
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=15\text{V}, R_L=0.75\Omega, R_{GEN}=1\Omega, V_{GS}=10\text{V}$	-	15	-	nS
Rise Time	t_r		-	16	-	nS
Turn-off Delay Time	$t_{d(off)}$		-	36	-	nS
Fall Time	t_f		-	13	-	nS
Total Gate Charge	Q_g	$V_{DS}=15\text{V}, V_{GS}=10\text{V}, I_D=20\text{A}$	-	26	-	nC
Gate-to-Source Charge	Q_{gs}		-	18	-	nC
Gate-to-Drain "Miller" Charge	Q_{gd}		-	28	-	nC
Diode Forward Voltage	V_{SD}	$I_S=3\text{A}, V_{GS}=0\text{V}$	-	0.75	-	V

Electrical Characteristics (P-Channel) at $T_a=25^{\circ}\text{C}$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=-250\mu\text{A}, V_{GS}=0\text{V}$	-40	-	-	V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-40\text{V}, V_{GS}=0\text{V}$	-	-	-1	μA
Gate-to-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20\text{V}, V_{DS}=0\text{V}$	-	-	± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu\text{A}$	-1	-2	-3	V
Static Drain-to-Source On-State Resistance	$R_{DS(ON)}$	$I_D=-1\text{A}, V_{GS}=-10\text{V}$	-	30	42	$\text{m}\Omega$
	$R_{DS(ON)}$	$I_D=-1\text{A}, V_{GS}=-4.5\text{V}$	-	49	70	$\text{m}\Omega$
Input Capacitance	C_{iss}	$V_{DS}=-15\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$	-	1020	-	pF
Output Capacitance	C_{oss}	$V_{DS}=-15\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$	-	180	-	pF
Reverse Transfer Capacitance	C_{rss}	$V_{DS}=-15\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$	-	120	-	pF
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=-15\text{V}, R_L=0.75\Omega, R_{GEN}=1\Omega, V_{GS}=10\text{V}$	-	16	-	nS
Rise Time	t_r		-	18	-	nS
Turn-off Delay Time	$t_{d(off)}$		-	49	-	nS
Fall Time	t_f		-	15	-	nS
Total Gate Charge	Q_g	$V_{DS}=-15\text{V}, V_{GS}=10\text{V}, I_D=-10\text{A}$	-	28	-	nC
Gate-to-Source Charge	Q_{gs}		-	21	-	nC
Gate-to-Drain "Miller" Charge	Q_{gd}		-	32	-	nC
Diode Forward Voltage	V_{SD}	$I_S=-3\text{A}, V_{GS}=0\text{V}$	-	-0.75	-	V

Typical Characteristics (N-Channel) at $T_a=25^\circ\text{C}$




Fig. 1 Typical Output Characteristic




Fig. 2 Typical Transfer Characteristics




Fig. 3 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 4 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 5 Typical On-Resistance vs. Drain Current and Temperature




Fig. 6 On-Resistance Variation with Temperature

Typical Characteristics (N-Channel) at $T_a=25^\circ\text{C}$ (Continued)




Fig. 7 On-Resistance Variation with Temperature




Fig. 8 Gate Threshold Variation vs. Ambient Temperature




Fig. 9 Diode Forward Voltage vs. Current




Fig. 10 Typical Junction Capacitance




Fig. 11 Gate Charge

Typical Characteristics (P-Channel) at $T_a=25^{\circ}\text{C}$




Figure 1 Typical Output Characteristics




Figure 2 Typical Transfer Characteristics




Figure 3 Typical On-Resistance vs. Drain Current and Gate Voltage




Figure 4 Typical On-Resistance vs. Drain Current and Temperature




Figure 5 On-Resistance Variation with Temperature




Figure 6 On-Resistance Variation with Temperature




Figure 7 Gate Threshold Variation vs. Ambient Temperature




Figure 8 Diode Forward Voltage vs. Current




Figure 9 Typical Junction Capacitance




Figure 10 Gate Charge Characteristics